Bohnenkamp 📕 🛑 Moving Professionals

TYRES

Product group	Tyres
Item number	15226893
Valid tyre size	VF 270 / 95 R 48
LI / SI / PR	155 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 363 +





Notes and features

- The Alliance 363+ is a VF row crop tyre for heavy, self-. propelled field sprayers and tractors.
- It offers up to 40% higher load capacity at the same • inflation pressure or the same load capacity at up to 40% reduced inflation pressure compared with a standard tyre.
- The directional tread pattern design, divided in separate . blocks, enables good grip on soft surfaces.
- The increased number of lugs and block distribution on • the tread pattern ensure good ride comfort and low rolling resistance on roads.
- Its large contact area provides high traction, reduced fuel • consumption and low soil compaction.
- The steel belted casing enables uniform ground pressure . distribution and protection against damages, thus ensuring a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15226893
EAN	7291050077217
Valid tyre size	VF 270 / 95 R 48
LI / SI / PR	155 D
	TL
Brand	Alliance
Tread pattern	Agriflex 363 +
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	93,56
Recommended rim size	DW10
Permitted rim size	DW9, W10
Maximum air pressure [bar].	4,00
Section width (mm)	280
Outer diameter of tyre [mm].	1740
Stat. radius (SLR) [mm]	822
Speed Radius Index (SRI)	850
Rolling circumference [mm].	5255
Tyre capacity 75% [ltr.]	171.75
Guarantee period	10 years
E-Ready	No

22.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 D	3875	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.