

## TYRES

|                 |               |
|-----------------|---------------|
| Product group   | Tyres         |
| Item number     | 15226942      |
| Valid tyre size | 200 / 65 R 16 |
| LI / SI / PR    | 94 A8 / 94 B  |
| TL/TT           | TL            |
| Brand           | Alliance      |
| Tread pattern   | 579           |



## Notes and features

- With regard to its design and tread pattern, the Alliance 579 is comparable to the Galaxy Garden Pro, a special tyre for small and medium tractors for the cultivation of grasslands, vineyards and fruit orchards.
- The especially high tread pattern depth, large quantity of tread blocks and the tread pattern design provide good traction, a long service life and good self-cleaning.
- Its open, rounded tyre shoulder and the large contact area reduce ground pressure and protect soil and crops.

## Technical Informations

|                              |               |
|------------------------------|---------------|
| Item number                  | 15226942      |
| EAN                          | 8903635029021 |
| Valid tyre size              | 200 / 65 R 16 |
| LI / SI / PR                 | 94 A8 / 94 B  |
| TL/TT                        | TL            |
| Brand                        | Alliance      |
| Tread pattern                | 579           |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | ECE 106       |
| Nettogewicht [kg] (gültig)   | 13,90         |
| Recommended rim size         | W6            |
| Maximum air pressure [bar].  | 2,40          |
| Section width (mm)           | 198           |
| Outer diameter of tyre [mm]. | 666           |
| Stat. radius (SLR) [mm]      | 309.00        |
| Rolling circumference [mm].  | 1968          |
| Tread depth (mm)             | 20,0          |
| E-Ready                      | No            |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 94 A8 | 670                | 40           |               | 2,40                     |              |
| 94 B  | 670                | 50           |               | 2,40                     |              |