

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 15226963       |
| Valid tyre size | 280 / 70 R 18  |
| LI / SI / PR    | 114 A8 / 114 B |
| TL/TT           | TL             |
| Brand           | Alliance       |
| Tread pattern   | 579            |



## Notes and features

- With regard to its design and tread pattern, the Alliance 579 is comparable to the Galaxy Garden Pro, a special tyre for small and medium tractors for the cultivation of grasslands, vineyards and fruit orchards.
- The especially high tread pattern depth, large quantity of tread blocks and the tread pattern design provide good traction, a long service life and good self-cleaning.
- Its open, rounded tyre shoulder and the large contact area reduce ground pressure and protect soil and crops.

## Technical Informations

|                              |                |
|------------------------------|----------------|
| Item number                  | 15226963       |
| EAN                          | 8903635029304  |
| Valid tyre size              | 280 / 70 R 18  |
| LI / SI / PR                 | 114 A8 / 114 B |
| TL/TT                        | TL             |
| Brand                        | Alliance       |
| Tread pattern                | 579            |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 28,95          |
| Recommended rim size         | W9             |
| Maximum air pressure [bar].  | 2,40           |
| Section width (mm)           | 282            |
| Outer diameter of tyre [mm]. | 849            |
| Stat. radius (SLR) [mm]      | 387            |
| Rolling circumference [mm].  | 2530           |
| Tread depth (mm)             | 24,0           |
| E-Ready                      | No             |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 114 A8 | 1180               | 40           |               | 2,40                     |              |
| 114 B  | 1180               | 50           |               | 2,40                     |              |