

## **TYRES**

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 15226972       |
| Valid tyre size | 380 / 70 R 20  |
| LI / SI / PR    | 122 A8 / 122 B |
| TL/TT           | TL             |
| Brand           | Alliance       |
| Tread pattern   | 579            |





## Notes and features

- With regard to its design and tread pattern, the Alliance 579 is comparable to the Galaxy Garden Pro, a special tyre for small and medium tractors for the cultivation of grasslands, vineyards and fruit orchards.
- The especially high tread pattern depth, large quantity of tread blocks and the tread pattern design provide good traction, a long service life and good self-cleaning.
- Its open, rounded tyre shoulder and the large contact area reduce ground pressure and protect soil and crops.



## **Technical Informations**

| Item number                  | 15226972       |
|------------------------------|----------------|
| EAN                          | 8903635046264  |
| Valid tyre size              | 380 / 70 R 20  |
| LI / SI / PR                 | 122 A8 / 122 B |
| TL/TT                        | TL             |
| Brand                        | Alliance       |
| Tread pattern                | 579            |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 55,60          |
| Recommended rim size         | W12            |
| Maximum air pressure [bar].  | 1,60           |
| Section width (mm)           | 380            |
| Outer diameter of tyre [mm]. | 1082           |
| Stat. radius (SLR) [mm]      | 501            |
| Rolling circumference [mm].  | 3236           |
| Tread depth (mm)             | 25,4           |
| E-Ready                      | No             |

## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 122 A8 | 1500               | 40           |               | 1,60                        |              |
| 122 B  | 1500               | 50           |               | 1,60                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.