

TYRES

Product group	Tyres
Item number	15227070
Valid tyre size	14.9 R 26
LI / SI / PR	127 A8 / 124 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356



Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.

- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.



Technical Informations

Item number	15227070
EAN	7291050017602
Valid tyre size	14.9 R 26
LI / SI / PR	127 A8 / 124 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	75,44
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	1,60
Section width (mm)	378
Outer diameter of tyre [mm].	1300
Stat. radius (SLR) [mm]	592
Rolling circumference [mm].	3857
Tread depth (mm)	43,0
Number of lugs	20x2
Lug width (mm)	35
Tyre capacity 75% [ltr.]	191.25
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 A8	1750	40		1,60	
124 B	1600	50		1,60	