

TYRES

Product group	Tyres
Item number	15227080
Valid tyre size	16.9 R 26
LI / SI / PR	135 A8 / 132 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.
- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.

Technical Informations

Item number	15227080
EAN	7291050017664
Valid tyre size	16.9 R 26
LI / SI / PR	135 A8 / 132 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	86,18
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	429
Outer diameter of tyre [mm].	1370
Stat. radius (SLR) [mm]	609
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4068
Tread depth (mm)	45,5
Number of lugs	19x2
Lug width (mm)	35
Tyre capacity 75% [litr.]	250.5
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 A8	2180	40		1,60	
132 B	2000	50		1,60	