

## **TYRES**

| Product group   | Tyres           |
|-----------------|-----------------|
| Item number     | 15227090        |
| Valid tyre size | 18.4 R 26       |
| LI / SI / PR    | 140 A8 / 137 B  |
| TL/TT           | TL              |
| Brand           | Alliance        |
| Tread pattern   | Power Drive 356 |



## Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.

- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.



## **Technical Informations**

| Item number                  | 15227090        |
|------------------------------|-----------------|
| EAN                          | 7291050017534   |
| Valid tyre size              | 18.4 R 26       |
| LI / SI / PR                 | 140 A8 / 137 B  |
| TL/TT                        | TL              |
| Brand                        | Alliance        |
| Tread pattern                | Power Drive 356 |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | ECE 106         |
| Nettogewicht [kg] (gültig)   | 107,84          |
| Recommended rim size         | 16              |
| Permitted rim size           | 15              |
| Maximum air pressure [bar].  | 1,60            |
| Section width (mm)           | 476             |
| Outer diameter of tyre [mm]. | 1426            |
| Stat. radius (SLR) [mm]      | 643             |
| Rolling circumference [mm].  | 4205            |
| Tread depth (mm)             | 45,0            |
| Number of lugs               | 20x2            |
| Lug width (mm)               | 38              |
| Tyre capacity 75% [ltr.]     | 305.25          |
| Guarantee period             | 7 years         |
| E-Ready                      | No              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 140 A8 | 2500               | 40           |               | 1,60                        |              |
| 137 B  | 2300               | 50           |               | 1,60                        |              |