

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 15227185       |
| Valid tyre size | 16.9 R 30      |
| LI / SI / PR    | 137 A8 / 134 B |
| TL/TT           | TL             |
| Brand           | Alliance       |
| Tread pattern   | 387            |



## Notes and features

- Agricultural tyre developed specifically for grassland and delicate soils.
- Ideal for landscape maintenance as well as fruit and viticulture.
- Concentrically-overlapping lugs for a larger contact area and thus lower ground pressure.
- Rounded lug shoulders for gentle driving on grasslands.
- High stability even when driving on slopes.

## Technical Informations

|                              |                |
|------------------------------|----------------|
| Item number                  | 15227185       |
| EAN                          | 8903635006329  |
| Valid tyre size              | 16.9 R 30      |
| Alternative size 1           | 440/80R30      |
| LI / SI / PR                 | 137 A8 / 134 B |
| TL/TT                        | TL             |
| Brand                        | Alliance       |
| Tread pattern                | 387            |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 92,84          |
| Recommended rim size         | 15             |
| Maximum air pressure [bar].  | 1,60           |
| Section width (mm)           | 429            |
| Outer diameter of tyre [mm]. | 1475           |
| Stat. radius (SLR) [mm]      | 667            |
| Rolling circumference [mm].  | 4357           |
| Tread depth (mm)             | 35,0           |
| Number of lugs               | 21x2           |
| Tyre capacity 75% [litr.]    | 261            |
| Guarantee period             | 7 years        |
| E-Ready                      | No             |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 137 A8 | 2300               | 40           |               | 1,60                     |              |
| 134 B  | 2120               | 50           |               | 1,60                     |              |