

TYRES

Product group	Tyres
Item number	15227202
Valid tyre size	12.4 R 32
LI / SI / PR	134 A8 / 131 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.
- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.

Technical Informations

Item number	15227202
EAN	7291050044226
Valid tyre size	12.4 R 32
LI / SI / PR	134 A8 / 131 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	63,68
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	2,90
Section width (mm)	315
Outer diameter of tyre [mm].	1350
Stat. radius (SLR) [mm]	627
Rolling circumference [mm].	4055
Tyre capacity 75% [ltr.]	146.25
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A8	2120	40		2,90	
131 B	1950	50		2,90	