

TYRES

Product group	Tyres
Item number	15227326
Valid tyre size	380 / 80 R 38
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	Alliance
Tread pattern	385



Notes and features

- Agricultural radial tyre of the 80/85 series for high-performance tractors up to approx. 200 hp.
- High air volume for enormous load capacity and excellent ride comfort.
- R-1W tread pattern (20% higher tread depth compared with R-1) in conjunction with optimum number of lugs for good traction and self-cleaning.
- Reinforced bead and lugs for a long service life.
- Stubble guard rubber compound provides protection against punctures caused by e.g. corn stubble.

Technical Informations

Item number	15227326
EAN	8903635012337
Valid tyre size	380 / 80 R 38
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	Alliance
Tread pattern	385
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	108,19
Recommended rim size	12
Permitted rim size	11, 13
Maximum air pressure [bar].	2,40
Section width (mm)	385
Outer diameter of tyre [mm].	1596
Stat. radius (SLR) [mm]	738
Rolling circumference [mm].	4781
Tread depth (mm)	45,0
Number of lugs	26x2
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		2,40	
142 B	2650	50		2,40	