

## **TYRES**

Product group	Tyres	
Item number	15227328	
Valid tyre size	IF 380 / 95 R 38	
LI / SI / PR	154 D TL	
TL/TT		
Brand	Alliance	
Tread pattern	Agriflex 354	



## Notes and features

- The Alliance Agriflex 354 is a row crop tyre with IF technology for tractors, self-propelled and towed field sprayers.
- As an IF tyre, it has 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs.
- Its large contact area and steel belt construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.



## **Technical Informations**

Item number	15227328
EAN	7291050065443
Valid tyre size	IF 380 / 95 R 38
LI / SI / PR	154 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	128,86
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	2,40
Section width (mm)	391
Outer diameter of tyre [mm].	1682
Stat. radius (SLR) [mm]	767
Rolling circumference [mm].	5018
Tread depth (mm)	48,0
Number of lugs	30x2
Tyre capacity 75% [ltr.]	270
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 D	3750	65		2,40	