

## TYRES

Product group	Tyres
Item number	15227330
Valid tyre size	15.5 R 38
LI / SI / PR	134 A8 / 131 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356



Bohnenkamp  
■ ■ ● Moving Professionals

 **ALLIANCE**  
ENGINEERED TO KEEP YOU AHEAD

## Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.
- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.

## Technical Informations

Item number	15227330
EAN	7291050044547
Valid tyre size	15.5 R 38
Alternative size 1	400/75R38
LI / SI / PR	134 A8 / 131 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	100,03
Recommended rim size	14
Maximum air pressure [bar].	1,60
Section width (mm)	394
Outer diameter of tyre [mm].	1570
Stat. radius (SLR) [mm]	723
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4751
Tread depth (mm)	44,0
Number of lugs	24x2
Lug width (mm)	36
Tyre capacity 75% [ltr.]	245.25
Guarantee period	7 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A8	2120	40		1,60	
131 B	1950	50		1,60	