

TYRES

Product group	Tyres
Item number	15227343
Valid tyre size	420 / 85 R 38
LI / SI / PR	144 A8 / 141 D
TL/TT	TL
Brand	Alliance
Tread pattern	385



Notes and features

- Agricultural radial tyre of the 80/85 series for high-performance tractors up to approx. 200 hp.
- High air volume for enormous load capacity and excellent ride comfort.
- R-1W tread pattern (20% higher tread depth compared with R-1) in conjunction with optimum number of lugs for good traction and self-cleaning.
- Reinforced bead and lugs for a long service life.
- Stubble guard rubber compound provides protection against punctures caused by e.g. corn stubble.

Technical Informations

Item number	15227343
EAN	7291050022651
Valid tyre size	420 / 85 R 38
Alternative size 1	16.9R38
LI / SI / PR	144 A8 / 141 D
TL/TT	TL
Brand	Alliance
Tread pattern	385
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	133,54
Recommended rim size	15
Permitted rim size	13, 14
Maximum air pressure [bar].	1,60
Section width (mm)	446
Outer diameter of tyre [mm].	1670
Stat. radius (SLR) [mm]	766
Rolling circumference [mm].	4990
Tyre capacity 75% [litr.]	308.25
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		1,60	
141 D	2575	65		1,60	