

TYRES

Product group	Tyres
Item number	15227343
Valid tyre size	420 / 85 R 38
LI / SI / PR	144 A8 / 141 D
TL/TT	TL
Brand	Alliance
Tread pattern	385





Notes and features

- Agricultural radial tyre of the 80/85 series for highperformance tractors up to approx. 200 hp.
- High air volume for enormous load capacity and excellent ride comfort.
- R-1W tread pattern (20% higher tread depth compared with R-1) in conjunction with optimum number of lugs for good traction and self-cleaning.
- Reinforced bead and lugs for a long service life.
- Stubble guard rubber compound provides protection against punctures caused by e.g. corn stubble.



Technical Informations

Item number	15227343
EAN	7291050022651
Valid tyre size	420 / 85 R 38
Alternative size 1	16.9R38
LI / SI / PR	144 A8 / 141 D
TL/TT	TL
Brand	Alliance
Tread pattern	385
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	133,54
Recommended rim size	15
Permitted rim size	13, 14
Maximum air pressure [bar].	1,60
Section width (mm)	446
Outer diameter of tyre [mm].	1670
Stat. radius (SLR) [mm]	766.00
Rolling circumference [mm].	4961
Tyre capacity 75% [ltr.]	308.25
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		1,60	
141 D	2575	65		1,60	