

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15227383 |
| Valid tyre size | 18.4 R 42 |
| LI / SI / PR | 169 A8 / 166 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Power Drive 356 |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.
- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 15227383 |
| EAN | 7291050050302 |
| Valid tyre size | 18.4 R 42 |
| LI / SI / PR | 169 A8 / 166 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Power Drive 356 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 187,50 |
| Recommended rim size | 16 |
| Permitted rim size | 15 |
| Maximum air pressure [bar]. | 4,50 |
| Section width (mm) | 467 |
| Outer diameter of tyre [mm]. | 1850 |
| Stat. radius (SLR) [mm] | 853 |
| Speed Radius Index (SRI) | 875 |
| Rolling circumference [mm]. | 5638 |
| Tread depth (mm) | 45,0 |
| Number of lugs | 24x2 |
| Tyre capacity 75% [ltr.] | 439.5 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 169 A8 | 5800 | 40 | | 4,50 | |
| 166 B | 5300 | 50 | | 4,50 | |