

TYRES

Product group	Tyres
Item number	15227383
Valid tyre size	18.4 R 42
LI / SI / PR	169 A8 / 166 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**

Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.
- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.

Technical Informations

Item number	15227383
EAN	7291050050302
Valid tyre size	18.4 R 42
LI / SI / PR	169 A8 / 166 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	187,50
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	4,50
Section width (mm)	467
Outer diameter of tyre [mm].	1850
Stat. radius (SLR) [mm]	853
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5638
Tread depth (mm)	45,0
Number of lugs	24x2
Tyre capacity 75% [ltr.]	439.5
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A8	5800	40		4,50	
166 B	5300	50		4,50	