

TYRES

Product group	Tyres
Item number	15227395
Valid tyre size	IF 520 / 85 R 42
LI / SI / PR	169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372



Bohnenkamp
■ ■ ● Moving Professionals

ALLIANCE
ENGINEERED TO KEEP YOU AHEAD

Notes and features

- The Alliance 372 is an IF tyre for high-performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.

Technical Informations

Item number	15227395
EAN	7291050066075
Valid tyre size	IF 520 / 85 R 42
LI / SI / PR	169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	223,50
Recommended rim size	16
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	538
Outer diameter of tyre [mm].	1951
Stat. radius (SLR) [mm]	870
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5772
Tread depth (mm)	55,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	569
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 D	5800	65		2,40	