

TYRES

Product group	Tyres
Item number	15227399
Valid tyre size	520 / 85 R 42
LI / SI / PR	168 A8 / 165 D
TL/TT	TL
Brand	Alliance
Tread pattern	385



Notes and features

- Agricultural radial tyre of the 80/85 series for high-performance tractors up to approx. 200 hp.
- High air volume for enormous load capacity and excellent ride comfort.
- R-1W tread pattern (20% higher tread depth compared with R-1) in conjunction with optimum number of lugs for good traction and self-cleaning.
- Reinforced bead and lugs for a long service life.
- Stubble guard rubber compound provides protection against punctures caused by e.g. corn stubble.

Technical Informations

Item number	15227399
EAN	7291050056960
Valid tyre size	520 / 85 R 42
Alternative size 1	20.8R42
LI / SI / PR	168 A8 / 165 D
TL/TT	TL
Brand	Alliance
Tread pattern	385
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	202,76
Recommended rim size	18
Maximum air pressure [bar].	2,80
Section width (mm)	538
Outer diameter of tyre [mm].	1956
Stat. radius (SLR) [mm]	901
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5947
Tyre capacity 75% [ltr.]	531
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		2,80	
165 D	5150	65		2,80	