

TYRES

·	
Product group	Tyres
Item number	15227423
Valid tyre size	18.4 R 46
LI / SI / PR	176 A8 / 176 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356



Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.

- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.



Technical Informations

Item number	15227423
EAN	7291050062053
Valid tyre size	18.4 R 46
LI / SI / PR	176 A8 / 176 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	190,97
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	3,50
Section width (mm)	467
Outer diameter of tyre [mm].	1958
Stat. radius (SLR) [mm]	906
Rolling circumference [mm].	5918
Tread depth (mm)	45,0
Tyre capacity 75% [ltr.]	635
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A8	7100	40		3,50	
176 B	7100	50		3,50	