

TYRES

Product group	Tyres
Item number	15227430
Valid tyre size	520 / 85 R 46
LI / SI / PR	173 A8 / 169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery.
- Aggressive R-1W tread pattern for maximum traction and low slip.
- Offers enormous load capacities even at low inflation pressures.
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example.

Technical Informations

Item number	15227430
EAN	7291050046442
Valid tyre size	520 / 85 R 46
Alternative size 1	20.8R46
LI / SI / PR	173 A8 / 169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	242,58
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	3,20
Section width (mm)	542
Outer diameter of tyre [mm].	2050
Stat. radius (SLR) [mm]	956
Speed Radius Index (SRI)	1025
Rolling circumference [mm].	6284
Tread depth (mm)	60,0
Number of lugs	23x2
Lug width (mm)	47
Tyre capacity 75% [ltr.]	580
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A8	6500	40		3,20	
169 D	5800	65		3,20	