Bohnenkamp Moving Professionals

20.09.2024

TYRES

| Product group | Tyres | |
|-----------------|-------------------|--|
| Item number | 15227520 | |
| Valid tyre size | 280 / 85 R 20 | |
| LI / SI / PR | 112 A8 / 112 B | |
| TL/TT | TL | |
| Brand | Alliance | |
| Tread pattern | FarmPRO Radial 85 | |



Notes and features

- Farm PRO row crop tyre of the 90 series for tractors and field sprayers.
- R-1W drive tread pattern and large contact area for good traction and low soil pressure.
- Improved driving stability for use even on slopes.
- Good self-cleaning properties due to dirt crushers between the lugs.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 15227520 |
|------------------------------|-------------------|
| | |
| EAN | 8903635007937 |
| Valid tyre size | 280 / 85 R 20 |
| Alternative size 1 | 11.2R20 |
| LI / SI / PR | 112 A8 / 112 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | FarmPRO Radial 85 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 35,68 |
| Recommended rim size | 10 |
| Permitted rim size | 9 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 288 |
| Outer diameter of tyre [mm]. | 984 |
| Stat. radius (SLR) [mm] | 447 |
| Rolling circumference [mm]. | 2913 |
| Tread depth (mm) | 37,0 |
| Number of lugs | 18x2 |
| Tyre capacity 75% [ltr.] | 67 |
| Guarantee period | 7 years |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 112 A8 | 1120 | 40 | | 1,60 | |
| 112 B | 1120 | 50 | | 1,60 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.