

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 15227596 |
| Valid tyre size | 380 / 85 R 26 |
| LI / SI / PR | 127 A8 / 127 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | FarmPRO II |



Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 15227596 |
| EAN | 8903635027447 |
| Valid tyre size | 380 / 85 R 26 |
| Alternative size 1 | 14.9R26 |
| LI / SI / PR | 127 A8 / 127 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | FarmPRO II |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 78,50 |
| Recommended rim size | W12 |
| Permitted rim size | W11 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 380 |
| Outer diameter of tyre [mm]. | 1290 |
| Stat. radius (SLR) [mm] | 594 |
| Rolling circumference [mm]. | 3800 |
| Tread depth (mm) | 45,0 |
| Number of lugs | 20x2 |
| Tyre capacity 75% [ltr.] | 162.51 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 127 A8 | 1750 | 40 | | 1,60 | |
| 127 B | 1750 | 50 | | 1,60 | |