Bohnenkamp Moving Professionals

21.09.2024

TYRES

Product group	Tyres
Item number	15227601
Valid tyre size	320 / 85 R 28
LI / SI / PR	124 A8 / 124 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II





Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number 15227601 EAN 8903635010494 Valid tyre size 320 / 85 R 28 Alternative size 1 12.4R28 LI / SI / PR 124 A8 / 124 B TL/TT TL Brand Alliance
Valid tyre size320 / 85 R 28Alternative size 112.4R28LI / SI / PR124 A8 / 124 BTL/TTTLBrandAlliance
Alternative size 1 12.4R28 LI / SI / PR 124 A8 / 124 B TL/TT TL Brand Alliance
LI / SI / PR 124 A8 / 124 B TL/TT TL Brand Alliance
TL/TT TL Brand Alliance
Brand Alliance
Tread pattern FarmPRO II
Antistatic No
Tyre colour Black
ECE regulation number ECE 106
Nettogewicht [kg] (gültig) 58,60
Recommended rim size 11
Permitted rim size 9, 10
Maximum air pressure [bar]. 1,60
Section width (mm) 325
Outer diameter of tyre [mm]. 1246
Stat. radius (SLR) [mm] 565
Rolling circumference [mm]. 3610
Tread depth (mm) 39,8
Number of lugs 20x2
Tyre capacity 75% [ltr.] 115
Guarantee period 7 years
E-Ready No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 A8	1600	40		1,60	
124 B	1600	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.