# Bohnenkamp Moving Professionals

21.09.2024

#### TYRES

Product group	Tyres
Item number	15227665
Valid tyre size	420 / 90 R 30
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II





#### Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	15227665
EAN	8903635013143
Valid tyre size	420 / 90 R 30
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	113,85
Recommended rim size	13
Permitted rim size	14
Maximum air pressure [bar].	2,40
Section width (mm)	418
Outer diameter of tyre [mm].	1518
Stat. radius (SLR) [mm]	684
Rolling circumference [mm].	4478
Tread depth (mm)	47,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	257
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40		2,40	
147 B	3075	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.