

TYRES

Product group	Tyres
Item number	15227678
Valid tyre size	320 / 85 R 34
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II



Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.

Technical Informations

Item number	15227678
EAN	8903635017349
Valid tyre size	320 / 85 R 34
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	72,80
Recommended rim size	11
Permitted rim size	W10
Maximum air pressure [bar].	2,40
Section width (mm)	325
Outer diameter of tyre [mm].	1407
Stat. radius (SLR) [mm]	650
Rolling circumference [mm].	4210
Tread depth (mm)	41,1
Number of lugs	26x2
Tyre capacity 75% [litr.]	146
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		2,40	
133 B	2060	50		2,40	