

## TYRES

|                 |                   |
|-----------------|-------------------|
| Product group   | Tyres             |
| Item number     | 15227788          |
| Valid tyre size | 320 / 80 R 42     |
| LI / SI / PR    | 141 A8 / 141 B    |
| TL/TT           | TL                |
| Brand           | Alliance          |
| Tread pattern   | FarmPRO Radial 80 |



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Agricultural tyre of the 85/80 series for tractors in the 50 to 160 performance range.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Good self-cleaning properties due to dirt crushers between the lugs.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.

## Technical Informations

|                              |                   |
|------------------------------|-------------------|
| Item number                  | 15227788          |
| EAN                          | 8903635011279     |
| Valid tyre size              | 320 / 80 R 42     |
| Alternative size 1           | 12.4R42           |
| LI / SI / PR                 | 141 A8 / 141 B    |
| TL/TT                        | TL                |
| Brand                        | Alliance          |
| Tread pattern                | FarmPRO Radial 80 |
| Antistatic                   | No                |
| Tyre colour                  | Black             |
| ECE regulation number        | ECE 106           |
| Nettogewicht [kg] (gültig)   | 86,15             |
| Recommended rim size         | W10               |
| Maximum air pressure [bar].  | 3,20              |
| Section width (mm)           | 319               |
| Outer diameter of tyre [mm]. | 1580              |
| Stat. radius (SLR) [mm]      | 751               |
| Speed Radius Index (SRI)     | 775               |
| Rolling circumference [mm].  | 4823              |
| Tread depth (mm)             | 42,0              |
| Number of lugs               | 31x2              |
| Tyre capacity 75% [ltr.]     | 133               |
| Guarantee period             | 7 years           |
| E-Ready                      | No                |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 141 A8 | 2575               | 40           |               | 3,20                     |              |
| 141 B  | 2575               | 50           |               | 3,20                     |              |