

TYRES

Product group	Tyres	
Item number	15227789	
Valid tyre size	320 / 90 R 42	
LI / SI / PR	147 A8 / 147 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	FarmPRO Radial 90	





Notes and features

- Farm PRO row crop tyre of the 90 series for tractors and field sprayers.
- R-1W drive tread pattern and large contact area for good traction and low soil pressure.
- Improved driving stability for use even on slopes.
- Good self-cleaning properties due to dirt crushers between the lugs.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.



Technical Informations

Item number	15227789
EAN	8903635012658
Valid tyre size	320 / 90 R 42
LI / SI / PR	147 A8 / 147 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO Radial 90
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	93,13
Recommended rim size	10
Maximum air pressure [bar].	3,60
Section width (mm)	319
Outer diameter of tyre [mm].	1643
Stat. radius (SLR) [mm]	764
Rolling circumference [mm].	4940
Tread depth (mm)	42,0
Number of lugs	36x2
Tyre capacity 75% [ltr.]	161
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 A8	3075	40		3,60	
147 B	3075	50		3,60	