Bohnenkamp Moving Professionals

22.09.2024

TYRES

Product group	Tyres
Item number	15227796
Valid tyre size	480 / 80 R 46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II





Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15227796
EAN	8903635013563
Valid tyre size	480 / 80 R 46
Alternative size 1	18.4R46
LI / SI / PR	158 A8 / 158 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	178,30
Recommended rim size	16
Maximum air pressure [bar].	2,40
Section width (mm)	479
Outer diameter of tyre [mm].	1960
Stat. radius (SLR) [mm]	880
Rolling circumference [mm].	5840
Tread depth (mm)	50,0
Tyre capacity 75% [ltr.]	401
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40		2,40	
158 B	4250	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.