

TYRES

Product group	Tyres	
Item number	15227800	
Valid tyre size	200 / 70 R 16	
LI / SI / PR	94 A8 / 94 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	370	





Notes and features

- Agricultural wide-base tyre of the 70 series for tractors in the low-performance range up to large tractors with over 200 hp.
- All-round tyre for use on farmland and grassland.
- Offers higher load capacities with the same inflation pressure in comparison to 85 standard tyres.
- R-1W drive tread pattern with higher tread depth for improved traction and high mileage.



Technical Informations

Item number	15227800
EAN	8903635006572
Valid tyre size	200 / 70 R 16
LI / SI / PR	94 A8 / 94 B
TL/TT	TL
Brand	Alliance
Tread pattern	370
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	14,28
Recommended rim size	6
Maximum air pressure [bar].	2,40
Section width (mm)	198
Outer diameter of tyre [mm].	686
Stat. radius (SLR) [mm]	315
Speed Radius Index (SRI)	330
Rolling circumference [mm].	2069
Tyre capacity 75% [ltr.]	19
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
94 A8	670	40		2,40	
94 B	670	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.