

TYRES

Product group	Tyres	
Item number	15227827	
Valid tyre size	400 / 75 R 38	
LI / SI / PR	134 A8 / 134 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	FarmPRO II	





Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.



Technical Informations

Item number	15227827
EAN	8903635022978
Valid tyre size	400 / 75 R 38
Alternative size 1	15.5R38
LI / SI / PR	134 A8 / 134 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	100,00
Recommended rim size	W13
Permitted rim size	W14L
Maximum air pressure [bar].	1,60
Section width (mm)	400
Outer diameter of tyre [mm].	1570
Stat. radius (SLR) [mm]	730
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4642
Tread depth (mm)	48,0
Number of lugs	22x2
Tyre capacity 75% [Itr.]	226.28
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A8	2120	40		1,60	
134 B	2120	50		1,60	