

## **TYRES**

Product group	Tyres	
Item number	15227832	
Valid tyre size	320 / 70 R 28	
LI / SI / PR	119 A8 / 119 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	FarmPRO Radial 70	





## Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.



## **Technical Informations**

Item number	15227832
EAN	8903635006602
Valid tyre size	320 / 70 R 28
LI / SI / PR	119 A8 / 119 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO Radial 70
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	56,83
Recommended rim size	10
Permitted rim size	11
Maximum air pressure [bar].	1,60
Section width (mm)	319
Outer diameter of tyre [mm].	1189
Stat. radius (SLR) [mm]	547
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3551
Tread depth (mm)	40,2
Number of lugs	21x2
Tyre capacity 75% [ltr.]	92
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
119 A8	1360	40		1,60	
119 B	1360	50		1,60	