

TYRES

Product group	Tyres
Item number	15227870
Valid tyre size	520 / 70 R 30
LI / SI / PR	145 A8 / 145 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO Radial 70



Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.

Technical Informations

Item number	15227870
EAN	8903635007913
Valid tyre size	520 / 70 R 30
LI / SI / PR	145 A8 / 145 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO Radial 70
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	132,57
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	1,60
Section width (mm)	516
Outer diameter of tyre [mm].	1536
Stat. radius (SLR) [mm]	691
Rolling circumference [mm].	4531
Tread depth (mm)	47,0
Number of lugs	16x2
Tyre capacity 75% [ltr.]	326
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		1,60	
145 B	2900	50		1,60	