

## **TYRES**

Product group	Tyres	
Item number	15227890	
Valid tyre size	480 / 70 R 38	
LI / SI / PR	145 A8 / 145 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	FarmPRO Radial 70	





## Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.



## **Technical Informations**

Item number	15227890
EAN	8903635007906
Valid tyre size	480 / 70 R 38
LI / SI / PR	145 A8 / 145 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO Radial 70
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	133,16
Recommended rim size	15
Permitted rim size	16
Maximum air pressure [bar].	1,60
Section width (mm)	479
Outer diameter of tyre [mm].	1681
Stat. radius (SLR) [mm]	770
Rolling circumference [mm].	4959
Tread depth (mm)	46,1
Tyre capacity 75% [ltr.]	334
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		1,60	
145 B	2900	50		1,60	