

TYRES

Product group	Tyres
Item number	15227900
Valid tyre size	520 / 70 R 38
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO Radial 70



Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.

Technical Informations

Item number	15227900
EAN	8903635007746
Valid tyre size	520 / 70 R 38
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO Radial 70
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	155,03
Recommended rim size	W16L
Permitted rim size	15, 18
Maximum air pressure [bar].	1,60
Section width (mm)	516
Outer diameter of tyre [mm].	1755
Stat. radius (SLR) [mm]	797
Rolling circumference [mm].	5076
Tread depth (mm)	47,0
Number of lugs	19x2
Lug width (mm)	43
Tyre capacity 75% [ltr.]	405
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		1,60	
150 B	3350	50		1,60	