

## TYRES

Product group	Tyres
Item number	15228795
Valid tyre size	520 / 85 R 42
LI / SI / PR	169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agri Star II



## Notes and features

- The Alliance Agri Star II is a new, modern agricultural tractor tyre with speed index "D" (up to 65 km/h) for tractors in all corresponding power ranges.
- The special Stratified Layer Technology provides very good traction and ride comfort in the field and on the road.
- Stratified Layer Technology combines 2 layers of agricultural lugs so that after initial wear of the external lugs, the lower layer of lugs continue to provide traction.
- Even after 40% wear, the 2nd lug layer guarantees good grip and effective traction and thus a long service life.
- The wide contact area ensures low soil compaction.
- The special abrasion- and puncture-resistant rubber compound (Stubble Guard) protects the tyre from damage caused by grain stubble.

## Technical Informations

Item number	15228795
EAN	8903635028796
Valid tyre size	520 / 85 R 42
LI / SI / PR	169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agri Star II
Carcass properties	Stubble Guard
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	209,47
Recommended rim size	DW16L
Permitted rim size	W16L, TW16L, W18L, DW18L
Maximum air pressure [bar].	3,60
Section width (mm)	520
Outer diameter of tyre [mm].	1952
Stat. radius (SLR) [mm]	909
Speed Radius Index (SRI)	975
Rolling circumference [mm].	5986
Tread depth (mm)	55,0
Number of lugs	23x2
Tyre capacity 75% [litr.]	555.98
Guarantee period	7 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 D	5800	65		3,60	