

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 15231067 |
| Valid tyre size | 12.0 - 18 |
| LI / SI / PR | 145 A6, 12 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 317 |



Notes and features

- Bias multi-purpose tyre for the most varied fields of application on a wide range of machines.
- Centrally-located tread bars for good vehicle handling on roads.
- Traction tread pattern for good traction and self-cleaning, even in difficult operation and weather conditions.
- Approved up to 90 km/h (G Speed Index).
- For longer, free-rolling use, mounting against the rolling direction is recommended.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 15231067 |
| EAN | 8903635009030 |
| Valid tyre size | 12.0 - 18 |
| LI / SI / PR | 145 A6, 12 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 317 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54 |
| Nettogewicht [kg] (gültig) | 40,02 |
| Recommended rim size | 9 |
| Permitted rim size | 11 |
| Maximum air pressure [bar]. | 4,50 |
| Section width (mm) | 294 |
| Outer diameter of tyre [mm]. | 949 |
| Stat. radius (SLR) [mm] | 420 |
| Rolling circumference [mm]. | 2770 |
| Tread depth (mm) | 23,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 145 A6 | 2900 | 30 | | 4,50 | |