## Bohnenkamp Moving Professionals

20.09.2024

### TYRES

Product group	Tyres
Item number	15231115
Valid tyre size	10.5 - 20
LI / SI / PR	131 G, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	317





#### Notes and features

- Bias multi-purpose tyre for the most varied fields of application on a wide range of machines.
- Traction tread pattern for good traction and self-cleaning, even in difficult operation and weather conditions.
- Centrally-located tread bars for good vehicle handling on roads.
- Approved up to 90 km/h (G Speed Index).
- For longer, free-rolling use, mounting against the rolling direction is recommended.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	15231115
EAN	8903635013280
Valid tyre size	10.5 - 20
LI / SI / PR	131 G, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	317
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	40,04
Recommended rim size	9
Maximum air pressure [bar].	4,30
Section width (mm)	270
Outer diameter of tyre [mm].	955
Stat. radius (SLR) [mm]	445
Rolling circumference [mm].	2880
Tread depth (mm)	20,9
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 G	1950	90		4,30	