

## TYRES

|                 |              |
|-----------------|--------------|
| Product group   | Tyres        |
| Item number     | 15231161     |
| Valid tyre size | 12.5 - 20    |
| LI / SI / PR    | 132 G, 12 PR |
| TL/TT           | TL           |
| Brand           | Alliance     |
| Tread pattern   | 317          |



## Notes and features

- Bias multi-purpose tyre for the most varied fields of application on a wide range of machines.
- Centrally-located tread bars for good vehicle handling on roads.
- Traction tread pattern for good traction and self-cleaning, even in difficult operation and weather conditions.
- Approved up to 90 km/h (G Speed Index).
- For longer, free-rolling use, mounting against the rolling direction is recommended.

## Technical Informations

|                              |               |
|------------------------------|---------------|
| Item number                  | 15231161      |
| EAN                          | 8903635013303 |
| Valid tyre size              | 12.5 - 20     |
| LI / SI / PR                 | 132 G, 12 PR  |
| TL/TT                        | TL            |
| Brand                        | Alliance      |
| Tread pattern                | 317           |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | ECE 54        |
| Nettogewicht [kg] (gültig)   | 45,45         |
| Recommended rim size         | 11            |
| Maximum air pressure [bar].  | 3,50          |
| Section width (mm)           | 325           |
| Outer diameter of tyre [mm]. | 1040          |
| Stat. radius (SLR) [mm]      | 475           |
| Rolling circumference [mm].  | 3090          |
| Tread depth (mm)             | 24,3          |
| E-Ready                      | No            |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 132 G | 2000               | 90           |               | 3,50                     |              |