

TYRES

Product group	Tyres
Item number	15231173
Valid tyre size	14.5 - 20
LI / SI / PR	136 G, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	317



Notes and features

- Bias multi-purpose tyre for the most varied fields of application on a wide range of machines.
- Centrally-located tread bars for good vehicle handling on roads.
- Traction tread pattern for good traction and self-cleaning, even in difficult operation and weather conditions.
- Approved up to 90 km/h (G Speed Index).
- For longer, free-rolling use, mounting against the rolling direction is recommended.

Technical Informations

Item number	15231173
EAN	8903635013228
Valid tyre size	14.5 - 20
LI / SI / PR	136 G, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	317
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	56,72
Recommended rim size	11
Permitted rim size	12
Maximum air pressure [bar].	3,00
Section width (mm)	355
Outer diameter of tyre [mm].	1095
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3260
Tread depth (mm)	24,3
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 G	2240	90		3,00	