

TYRES

Product group	Tyres
Item number	15231202
Valid tyre size	16 / 70 - 20
LI / SI / PR	145 G, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	317 (Spacer)



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**
ENGINEERED TO KEEP YOU AHEAD

Notes and features

- Bias multi-purpose tyre for the most varied fields of application on a wide range of machines.
- Centrally-located tread bars for good vehicle handling on roads.
- Special tread pattern with angular blocks in the tread centre with bigger distance (spacers) between the lugs.
- For longer, free-rolling use, mounting against the rolling direction is recommended.
- Traction tread pattern for good traction and self-cleaning, even in difficult operation and weather conditions.

Technical Informations

Item number	15231202
EAN	8903635013242
Valid tyre size	16 / 70 - 20
Alternative size 1	405/70-20
LI / SI / PR	145 G, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	317 (Spacer)
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	64,00
Recommended rim size	13
Maximum air pressure [bar].	3,50
Section width (mm)	407
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	791
Rolling circumference [mm].	3200
Tread depth (mm)	17,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 G	2900	90		3,50	