

TYRES

Product group	Tyres	
Item number	15231210	
Valid tyre size	405 / 70 - 20	
LI / SI / PR	149 B, 14 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Traction Industrial 323	



Notes and features

- The Alliance 323 is an industrial tyre with a wide range of possible uses.
- The extra deep tread pattern offers excellent traction and low wear.
- The asymmetric tread pattern design has impressive selfcleaning properties.
- The tyre was developed for use in agriculture, industry and on construction sites.
- Suitable for telescopic loaders, skid steer loaders or combine harvesters (rear axle).



Technical Informations

Item number	15231210
EAN	8903635004325
Valid tyre size	405 / 70 - 20
Alternative size 1	16.0/70-20
LI / SI / PR	149 B, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Traction Industrial 323
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	64,21
Recommended rim size	13
Maximum air pressure [bar].	3,50
Section width (mm)	407
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	496
Rolling circumference [mm].	3160
Tread depth (mm)	33,0
Number of lugs	16x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 B	3250	50		3,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.