

TYRES

Product group	Tyres
Item number	15231500
Valid tyre size	340 / 80 - 20
LI / SI / PR	144 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Tough Trac 325



Notes and features

- The Alliance 325 Tough Trac has a special directional tread pattern with solid lugs and excellent traction in all areas of application.
- The additionally strengthened sidewall and bead ensure optimum protection to minimise damage when used in heavy duty applications.
- The robust bias construction ensures stability in the demanding lifting mode.
- Most suitable for use with backhoe loaders among others.

Technical Informations

Item number	15231500
EAN	8903635013426
Valid tyre size	340 / 80 - 20
Alternative size 1	12.5/80-20
LI / SI / PR	144 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Tough Trac 325
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	61,32
Recommended rim size	11
Permitted rim size	10, 12
Maximum air pressure [bar].	4,00
Section width (mm)	340
Outer diameter of tyre [mm].	1045
Stat. radius (SLR) [mm]	473
Rolling circumference [mm].	3088
Tread depth (mm)	26,5
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		4,00	