

TYRES

Product group	Tyres
Item number	15231510
Valid tyre size	440 / 80 - 24
LI / SI / PR	168 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Tough Trac 325



Notes and features

- The Alliance 325 Tough Trac has a special directional tread pattern with solid lugs and excellent traction in all areas of application.
- The additionally strengthened sidewall and bead ensure optimum protection to minimise damage when used in heavy duty applications.
- The robust bias construction ensures stability in the demanding lifting mode.
- Most suitable for use with backhoe loaders among others.

Technical Informations

Item number	15231510
EAN	8903635013525
Valid tyre size	440 / 80 - 24
Alternative size 1	16.9-24
LI / SI / PR	168 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Tough Trac 325
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	103,23
Recommended rim size	14
Maximum air pressure [bar].	5,00
Section width (mm)	460
Outer diameter of tyre [mm].	1328
Stat. radius (SLR) [mm]	603
Rolling circumference [mm].	3933
Tread depth (mm)	34,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40		5,00	