

## TYRES

Product group	Tyres
Item number	15235226
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Alliance
Tread pattern	585



## Notes and features

- The Alliance 585 was developed for telehandlers, backhoe and compact loaders.
- It is suitable for use in agriculture as well as on construction sites.
- The large, non-directional tread pattern provides good traction and great performance even on hard surfaces.
- The high tread depth guarantees a long tyre life and good protection against tyre damage.

## Technical Informations

Item number	15235226
EAN	8903635027591
Valid tyre size	460 / 70 R 24
Alternative size 1	17.5LR24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Alliance
Tread pattern	585
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	103,60
Recommended rim size	DW15L
Permitted rim size	DW14L, DW16L, 14, 16, TW14L
Maximum air pressure [bar].	4,00
Section width (mm)	471
Outer diameter of tyre [mm].	1242
Stat. radius (SLR) [mm]	560
Rolling circumference [mm].	3704
Tread depth (mm)	35,0
Number of lugs	24x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,00	
159 B	4375	50		4,00	