

TYRES

Product group	Tyres	
Item number	15235235	
Valid tyre size	495 / 70 R 24	
LI / SI / PR	155 G	
TL/TT	TL	
Brand	Alliance	
Tread pattern	570	





Notes and features

- Radial multipurpose tyre for a wide variety of applications.
- Specially suited for use on harvesters.
- Agricultural tractor pattern for good traction when operating on arable land.
- High load capacities even with low inflation pressures.
- Radial textile casing with steel belt reinforcement.



Technical Informations

Item number	15235235
EAN	7291050048019
Valid tyre size	495 / 70 R 24
LI / SI / PR	155 G
TL/TT	TL
Brand	Alliance
Tread pattern	570
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	119,24
Recommended rim size	16
Maximum air pressure [bar].	4,00
Section width (mm)	499
Outer diameter of tyre [mm].	1304
Stat. radius (SLR) [mm]	588
Rolling circumference [mm].	3845
Tread depth (mm)	36,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 G	3875	90		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.