

TYRES

Product group	Tyres
Item number	15235237
Valid tyre size	500 / 70 R 24
LI / SI / PR	155 A8 / 164 A8
TL/TT	TL
Brand	Alliance
Tread pattern	570



Notes and features

- Radial multipurpose tyre for a wide variety of applications.
- Specially suited for use on harvesters.
- Agricultural tractor pattern for good traction when operating on arable land.
- High load capacities even with low inflation pressures.
- Radial textile casing with steel belt reinforcement.

Technical Informations

Item number	15235237
EAN	7291050060455
Valid tyre size	500 / 70 R 24
LI / SI / PR	155 A8 / 164 A8
TL/TT	TL
Brand	Alliance
Tread pattern	570
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	111,12
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	3,40
Section width (mm)	495
Outer diameter of tyre [mm].	1312
Stat. radius (SLR) [mm]	569
Rolling circumference [mm].	3905
Tread depth (mm)	34,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40	Drive Wheel	3,40	
164 A8	5000	40	Free Rolling	3,40	