

## **TYRES**

Product group	Tyres
Item number	15235240
Valid tyre size	500 / 85 R 24
LI / SI / PR	158 A8 / 171 A8
TL/TT	TL
Brand	Alliance
Tread pattern	570





## **Notes and features**

- Radial multipurpose tyre for a wide variety of applications.
- Specially suited for use on harvesters.
- Agricultural tractor pattern for good traction when operating on arable land.
- High load capacities even with low inflation pressures.
- Radial textile casing with steel belt reinforcement.



## **Technical Informations**

Item number	15235240
EAN	7291050050340
Valid tyre size	500 / 85 R 24
LI / SI / PR	158 A8 / 171 A8
TL/TT	TL
Brand	Alliance
Tread pattern	570
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	133,76
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	2,80
Section width (mm)	528
Outer diameter of tyre [mm].	1458
Stat. radius (SLR) [mm]	625
Rolling circumference [mm].	4365
Tread depth (mm)	44,5
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40	Drive Wheel	2,80	
171 A8	6150	40	Free Rolling	2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.