

TYRES

Product group	Tyres
Item number	15235241
Valid tyre size	500 / 85 R 24
LI / SI / PR	158 A8 / 171 A8
TL/TT	TL
Brand	Alliance
Tread pattern	570



Notes and features

- Radial multipurpose tyre for a wide variety of applications.
- Specially suited for use on harvesters.
- Agricultural tractor pattern for good traction when operating on arable land.
- High load capacities even with low inflation pressures.
- Radial textile casing with steel belt reinforcement.

Technical Informations

Item number	15235241
EAN	8903635013488
Valid tyre size	500 / 85 R 24
LI / SI / PR	158 A8 / 171 A8
TL/TT	TL
Brand	Alliance
Tread pattern	570
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	139,70
Recommended rim size	W16L
Permitted rim size	W15L
Maximum air pressure [bar].	2,80
Section width (mm)	528
Outer diameter of tyre [mm].	1458
Stat. radius (SLR) [mm]	625
Rolling circumference [mm].	4365
Tread depth (mm)	35,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A8	4250	40	Drive Wheel	2,80	
171 A8	6150	40	Free Rolling	2,80	