

TYRES

| Product group | Tyres | |
|-----------------|-----------------|--|
| Item number | 15235260 | |
| Valid tyre size | 620 / 70 R 30 | |
| LI / SI / PR | 166 A8 / 178 A8 | |
| TL/TT | TL | |
| Brand | Alliance | |
| Tread pattern | 570 | |





Notes and features

- Radial multipurpose tyre for a wide variety of applications.
- Specially suited for use on harvesters.
- Agricultural tractor pattern for good traction when operating on arable land.
- High load capacities even with low inflation pressures.
- Radial textile casing with steel belt reinforcement.



Technical Informations

| Item number | 15235260 |
|------------------------------|-----------------|
| EAN | 7291050061445 |
| Valid tyre size | 620 / 70 R 30 |
| LI / SI / PR | 166 A8 / 178 A8 |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 570 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 173,19 |
| Recommended rim size | 20 |
| Permitted rim size | 18 |
| Maximum air pressure [bar]. | 2,50 |
| Section width (mm) | 608 |
| Outer diameter of tyre [mm]. | 1622 |
| Stat. radius (SLR) [mm] | 727 |
| Rolling circumference [mm]. | 4835 |
| Tread depth (mm) | 47,0 |
| Tyre capacity 75% [ltr.] | 666 |
| Guarantee period | 10 years |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 166 A8 | 5300 | 40 | Drive Wheel | 2,50 | |
| 178 A8 | 7500 | 40 | Free Rolling | 2,50 | |