

TYRES

Product group	Tyres
Item number	15235800
Valid tyre size	24 R 20.5
LI / SI / PR	176 F
TL/TT	TL
Brand	Alliance
Tread pattern	392





Notes and features

- The Alliance 392 is a flotation tyre for heavy agricultural trailers, spreader trucks, agri-trucks and similar vehicles.
- The tyre was developed for on- and off-road use, whereby road use should be predominant.
- Its non-directional tread pattern provides a large contact area and optimum soil protection.
- The wide distances between the blocks ensure good selfcleaning properties.
- Inter-block bridges and a special strong rubber compound ensure even wear and a long service life.
- The all-steel casing protects the tyre against damages in difficult conditions.



Technical Informations

Item number	15235800
EAN	7291050066631
Valid tyre size	24 R 20.5
LI / SI / PR	176 F
TL/TT	TL
Brand	Alliance
Tread pattern	392
Carcass properties	All-Steel,HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	186,00
Recommended rim size	18.00
Maximum air pressure [bar].	6,00
Section width (mm)	600
Outer diameter of tyre [mm].	1372
Stat. radius (SLR) [mm]	624
Rolling circumference [mm].	4221
Tread depth (mm)	17,6
Number of lugs	32x2
Tyre capacity 75% [ltr.]	411.75
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 F	7100	80		6,00	